

Drain Air Gaps

For a long time now we have had customers asking for an air gap for the drain connection on softeners and RO's which complies with the relevant regulation. There have been various items available (mainly products made for the American market) but they tend to be large and expensive and are not WRAS listed. We now have the answer !!! This product has been developed for the British market and has been tested and listed under the WRAS scheme. You can now be confident that if an inspector visits one of your installations you will no longer have a non-approved drain connection. This fitting has a lot of benefits, a few of which are listed here:-

Reasonable cost

Small size

Can be used for softeners and/or RO's

Optional saddle and trap

Unique design allows fitment to any make of 11/2" waste pipe

Is available for 3/8" or 1/2" drain line, both have 1/4" str spigot for RO connection Easy to install - simply make a normal stand pipe with trap (or tee into an existing one) and solvent weld or silicone into place.

Alternatively use the Gap Trap Kit on existing waste pipes.

P920	Drain Air Gap 1/2" Barb	2.10
P921	Drain Air Gap 3/8" Speedfit	2.10
P950	Gap Trap Kit 1/2"	12.65
	Gap Trap Kit 3/8"	12.65



Plumbing Out Kits

The ever popular plumbing out kit (P162) which is for 1/2" drain hose is now available with a 3/8" adaptor (P906) for softeners having a 3/8" drain line. Part no for the kit with both 1/2" & 3/8" adaptors is P907. Alternatively buy the adaptor separately and keep for the odd occasion when vou need it.



P162	Plumbing out Kit	6.52
P906	3/4" B.S.P. x 3/8" Speedfit Adaptor	1.68
P907	Plumbing Out Kit 3/8" & 1/2"	8.20

Mini Stand Pipe Kit

This fast flow kit is widely used for the drain connection for water softeners. Its versatility and universal fitting means it will suit most applications. Supplied with cutting tool.




P166 Mini Stand-pipe Kit

7.98

Drain Vent

P164. Should you need to run drain hose outside install this as as close to the softener as



P164

freezing. Take note of direction arrows and secure with 'O' clips or Herbie clips.

P164 Drain Vent

1.65

Drain Elbows

Many softeners have a female connection for the drain outlet. Use these to connect to standard hose. All have 1/2" hose barb. Available with 1/4", 3/8", 1/2" or 3/4" B.S.P. thread.



P645	1/4" B.S.P. x 1/2" Hose Barb Elbow	0.98
P649	3/4" B.S.P. x 1/2" Hose Barb Elbow	1.02
P671	1/2" B.S.P. x 1/2" Hose Barb Elbow	1.71
P681	3/8" BSP x 1/2" Hose Barb Elbow	0.83

Overflow Elbow

P646. Simple water softener 1/2" brine tank elbow.



P646 1/2" Overflow Elbow

0.95